



Models	Capacity	Grease Capacity	Wall Thickness	A	B	C *	D	E	F *	ETL
	Guspm [LPM]	LB. [kg]	in [mm]	Inlet and outlet	Bottom to center	Center to top	Width	Length	Height	
CA-SG10-E-RS2	10 [38]	20 [9.0]	1/2 [13]	DN 2 in.	8 ½ [216]	6 [152]	14 [356]	17 [432]	14 ½ [368]	MEETS STANDARDS
CA-SG15-E-RS2	15 [57]	30 [13.6]	1/2 [13]	DN 2 in.	10 [254]	6 [152]	17 [432]	19 [483]	16 [406]	
CA-SG20-E-RS2	20 [76]	40 [18.1]	1/2 [13]	DN 3 in.	12 [305]	6 [152]	20 [508]	24 [610]	18 [457]	
CA-SG25-E-RS2	25 [95]	50 [22.7]	1/2 [13]	DN 3 in.	14 [356]	6 [152]	20 [508]	24 [610]	20 [508]	
CA-SG35-E-RS2	35 [132]	70 [31.7]	1/2 [13]	DN 4 in.	15 [381]	6 [152]	25 [635]	28 [711]	21 [533]	
CA-SG50-E-RS2	50 [189]	100 [45.3]	1/2 [13]	DN 4 in.	17 [432]	6 [152]	25 [635]	28 [711]	23 [584]	
CA-SG75-E-RS2	75 [284]	150 [67.5]	3/4 [19]	DN 4 in.	19 [483]	6 [152]	29 [737]	31 [787]	25 [635]	
CA-SG100-E-RS2	100 [378]	200 [90.0]	3/4 [19]	DN 4 in.	23 [584]	10 [254]	34 [864]	43 [1092]	33 [838]	
CA-SG150-E-RS2	150 [568]	300 [135]	3/4 [19]	DN 4 in.	25 [635]	10 [254]	42 [1067]	56 [1422]	35 [889]	**
CA-SG200-E-RS2	200 [757]	400 [181]	3/4 [19]	DN 4 in.	30 [762]	10 [254]	44 [1118]	61 [1549]	40 [1016]	**
CA-SG250-E-RS2	250 [946]	500 [227]	3/4 [19]	DN 4 in.	36 [914]	10 [254]	52 [1321]	71 [1803]	46 [1168]	**
CA-SG300-E-RS2	300 [1136]	600 [272]	3/4 [19]	DN 6 in.	39 [990]	10 [254]	53 [1346]	76 [1930]	49 [1245]	**

Note: Larger capacity available on request. * Dimension "C" can vary according to needs and dimension "F" will be modified in consequence.

** CSA B481 approval is not necessary for models with more than 100 gallons per minute (GPM)

DESCRIPTION

Recessed polypropylene grease interceptor including a flow regulator, removable baffle, integral trap with cleanout plug, fixed baffle retaining solids, (2x) suction connections, and bolted slip-resistant aluminium cover with neoprene gasket.

OPTIONS

- SBG** Grease biodegradation system
- CR** Reinforced cover
- DG** Grease detecting system with control panel (not available for SG10, 15 & 20)
- DG-CS** Dry contact grease detecting system (not available for SG10, 15 & 20)
- RS** Suction connection
- CRG** Galvanized reinforced cover
- RS(2)** 2 Suction connections
- CES** Superior seal frame/cover
- BA** Anchor flange